

#### 

Stitch Overview

The bernette 48 is the top model in the Funlock series and is a combination of an overlock and a coverstitch machine. It offers a total of 23 stitches: 15 overlock stitches, 3 coverstitches,


- 4 combo stitches and 1 chain stitch, the overlock stitches with a stitch width of up to 7 mm. The threading is facilitated by colorcoded threading paths, and a manual threader supports the threading of the needle eye. The looper threads are threaded mechanically. The knife is operated from below and thus
- provides not only a clean cutting edge but also safe handling and good visibility to the stitching. The b48 Funlock sews at a speed of up to 1300 stitches per minute.

LED light for optimal visibility

Differential feed

Knife drive from below for better visibility and safety







# High stitch quality with speeds of up to 1300 stitches per minute

Modern, two-color

Swiss Design

bernette

Practical carrier handle

### Color-coded theading paths for easier threading

Spacious working area (87 mm)

#### Accessories in looper cover

Safety switch is activated when looper cover is open

Large cut-offs bin included



## www.mybernette.com





.

**A A** 

.

.

🔺 🔺

▲

.

.

.

# Dernette 42 Funlock

The bernette 42 Funlock is a coverstitch machine with a total of 4 coverstitches. Professional stitches on seams, cuffs and bindings give your sewing project a perfect look. Particularly stretchy fabrics or thin knitwear such as jersey can be handled perfectly with the bernette 42. The threading of the needle and looper is supported by a mechanical looper threader and a manual needle threader. And a bright LED light ensures excellent visibility on the large work surface.

**A A** 

ernette

-

b42 FUNLOCK

.

.

▲ ▲

#### bernette 44 Funlock Overlock machine

.

.

The bernette 44 offers numerous practical functions which enable you to easily enter into the world of overlock stitching. With 15 stitches, it offers a compact stitch package. The fine

**A A** 

**A A** 

▲ ▲

**A A** 

**A A** 

**A A** 

▲

b44 FUNLOCK

.

**A** 


- adjustment of the stitches can be performed comfortably by turning a knob. Threading is supported by color-coded threading paths as well as looper and needle threading aids. The knife is operated from below for visibility while stitching and added safety. The bright LED light ensures good visi-
- bility. The b44 is also fast it stitches up to 1300 stitches per minute.

Would you like to sew your own clothing that looks perfect inside and out? Then the stylish bernette Funlock models, with their modern Swiss design, are perfect for you. With them you can take care of cutting, neatening and sewing all in one step. They are the perfect addition to a sewing machine and give your clothing a professional finish. Decide for yourself whether a coverstitch expert machine or an overlock machine fits best in your sewing studio – or a combination model with both. The bernette Funlock models are easy to operate, have impressive stitch quality and high durability, and are attractively priced. Experience creative sewing enjoyment at the highest level.

#### Stitch Overview



Stitch Overview



Schedar Safety sitch	Stitch patterns	b48	b44	b42	
Schreid aftry sitch Schrei	Total number of stitch patterns	23	15	4	Discover the three new bernette
a thread of who delivery       Image of who delivery         3 thread versitis his wideharrow)       Image of who delivery         3 thread versitis his wideharrow)       Image of who delivery         3 thread versitis his wideharrow)       Image of who delivery         3 thread versitis his wideharrow)       Image of who delivery         3 thread flattick (wideharrow)       Image of who delivery         3 thread versitis his wideharrow)       Image of who delivery         3 thread versitis his wideharrow)       Image of who delivery         3 thread versitis his wideharrow)       Image of who delivery         3 thread versitis his wideharrow)       Image of who delivery         3 thread versitis his wideharrow)       Image of who delivery         3 thread versitis his wideharrow)       Image of who delivery         3 thread versitis his wideharrow)       Image of who delivery         3 thread versitis his wideharrow)       Image of who delivery         3 thread versitis his wideharrow)       Image of who delivery         3 thread versitis his wideharrow)       Image of who delivery         3 thread versitis his wideharrow)       Image of who delivery         3 thread versitis his wideharrow)       Image of who delivery         3 thread versitis his wideharrow)       Image of were wideharrow         3 thread versitis his widehar	5-thread safety stitch	~	-	-	Funlock models in a modern
Anthone of Hondox         Color         Color         Color           3 thread 2 coversitith         Color         Color         Color           3 thread 2 coversitith (wide/harrow)         Color         Color         Color           3 thread decode(wide/harrow)         Color         Color         Color           3 thread decode(wide/harrow)         Color         Color         Color           3 thread fields (wide/harrow)         Color         Color         Color           3 thread decode(wide/harrow)         Color         Color         Color           3 thread decode(wide/harrow)         Color         Color         Color           3 thread decode(wide/harrow)         Color         Color         Color           3 thread fields (wide/harrow)         Color         Color         Color           3 thread field field         Color         Color         Color           2 thread vacaging opaths         Color         Color         Color           2 thread field field wile seveng         Color         Color         Color           3 thread field bell decode         Color         Color         Color           3 thread field bell decode         Color         Color         Color           3 thread field threading system<	4-thread safety stitch	~	-	-	
3 thread averack (wide/harrow)            2 thread dwnitch            2 thread dwnitch            2 thread dwnitch (wide/harrow)            2 thread may system            1 thread may system            2 thread may system            2	4-thread overlock	~	~	-	
3 thread overlock (vide/narrow)       -         3 thread subjectifieth       -         2 thread	4-thread/3-needle coverstitch	~	-	~	
3 thread super-stretch            3 thread statuck (wide/narrow)            3 thread nalis the            3 thread nalis the            2 thread nalis the            1 thread the            1 thread thread nalis the            2 thread nalis nalis the            2 thre	3-thread/2-needle coverstitch (wide/narrow)	~	-	~	
3 thread finations (wide/inarrow)       ···       ···       ···         3 thread finations (wide/inarrow)       ···       ···       ···         2 thread finati	3-thread overlock (wide/narrow)	~	~	-	
3-thread narrow saam   3-thread narrow saam   3-thread narrow saam   2-thread flattok: (wide/narrow)   2-thread flattok: (wide/narrow)<	3-thread super-stretch	~	~	-	
3 thread noiled hem           2 thread noiled ham statch           2 thread noiled ham           Coor coded threading paths           Low in threading system           Thread noils ne relaxes when presser foot rated           Stelley switch activated when cover open           Tencial Dat            Corentick width 3-7 mm            Caster drive width 3-7 mm            Stele noile noilevering gated	3-thread flatlock (wide/narrow)	~	~	-	
2-thread chain stitch            2-thread chain stitch            2-thread chain stitch            2-thread chain stitch            2-thread threading hains            2-thread threading paths            Liver threading system            Liver threading system            Liver threading system            Liver threading system            Liver thread threading paths            Liver thread threading paths            Liver thread threading paths            Liver thread threading paths            Stich length adjustable while serving            Accessories in looper cover            Stich length adjustable while serving system            Coentick while 3-10 nm <td>3-thread narrow seam</td> <td>~</td> <td>~</td> <td>-</td> <td></td>	3-thread narrow seam	~	~	-	
2-thread overlock (wide/narrow)           2-thread filtatick (wide/narrow)           2-thread rolled hem           Cohor of Fatures           Low in threading spaths           Color-coded threading spaths           Stick hength adjustable while sevents           Accessories in looper cover           Stick hength adjustable while sevent           Stick hength adjustable while sevent           Coverslick hwidth 3-7 mm           Coverslick hwidth 3-7 mm           Coverslick hwidth 3-7 mm           State spress froot measure           State spress froot measure           State darkackersories	3-thread rolled hem	~	~	-	
2-thread flatlock (wide/harrow) -   2-thread rolled hem rolled -   2-thread role hem role rolled -	2-thread chain stitch	~	-	~	
2-thread rolled hem           2-thread wrapped overlock (wide/narrow)           Comfort Features           Lower looper threader           Colo-coded threading paths           Lowin threading system           Lower looper threader           Stahd and vatable while sewing           Accessories            Stahd switch activated when cover open            Stahd vatable witch witch 3.40 S.6 mm            Combo sitch witch 3-10 mm            Stahad	2-thread overlock (wide/narrow)	~	~	-	
2-thread wrapped overlock (wide/harrow)       ·       ·       ·         Comfort Features       ·       ·       ·         Lower looper threader       ·       ·       ·         Color coded threading paths       ·       ·       ·         Lay-in threading system       ·       ·       ·         Thread tension release when presser foot raised       ·       ·       ·         Accessories in looper cover       ·       ·       ·       ·         Steth length adjustable while sewing       ·       ·       ·       ·         Accessories in looper cover       ·       ·       ·       ·       ·         Steth length adjustable while sewing       ·       ·       ·       ·       ·         Corestict width 3-70 mm       ·	2-thread flatlock (wide/narrow)	~	~	-	
Confort FeaturesImage: StemImage: StemImage	2-thread rolled hem	~	~	-	
Lower looper threaderImage: systemImage: systemImage: systemLay-in threading pathsImage: systemImage: systemImage: systemLay-in threading systemImage: systemImage: systemImage: systemThread tension release when presser foot raisedImage: systemImage: systemStoch leight adjustable while sewingImage: systemImage: systemAccessories in looper coverImage: systemImage: systemSewing lightImage: systemImage: systemSewing lightImage: systemImage: systemStoch activated when cover openImage: systemImage: systemOverfock seam width 3-7 mmImage: systemImage: systemCoverstitch width 2.8/5,6 mmImage: systemImage: systemStandard overlock presser footImage: systemImage: system<	2-thread wrapped overlock (wide/narrow)	~	~	-	
Color-coded threading paths····Lay-in threading system····Thread tension release when presser foot raised····Sitch length adjustable while sewing····Accessories in looper cover····Safety switch activated when cover open····Chrind Data·····Overfock seam width 3-7 mm····Coverstitch width 2,8/5,6 mm····Coverstitch width 3,-10 mm····Shinde diver from below····Standard Accessories····Standard Accessories····Standard overlock presser foot····Standard overlock presser foot····Standard overlock presser foot····Standard overlock presser foot····Cur-offs bin·····Needle set (ELX 705)······Tokandar accessories in senarate box·····Tokandar accessories in senarate box·····Tokandar accessories in senarate box·····Tokandar accessories in senarate box···	Comfort Features				
Lay-in threading system V V V V Thread tension release when presser foot raised V V V V Construction looper cover C V V V V Coversitic width 2,8/5,6 mm V V V Coversitich width 2,8/5,6 mm V V V V V Coversitich width 2,8/5,6 mm V V V V V V V V V V V V V V V V V V	Lower looper threader	~	~	-	
Thread tension release when presser foot raised -   Stitch length adjustable while sewing -   Accessories in looper cover -   Sewing light LED   Safety switch activated when cover open -     Sevind light -   Safety switch activated when cover open -     Coversitch width 3-7 mm -     Coversitch width 2.8/5.6 mm -     Coversitch width 3-10 mm -     Knife drive from below -     Atter from below -     Atter from below -     Relled hem lever integrated into stitch plate -   Standard overlock pressure -   Standard overlock presser foot -   Upper looper converter -   Manual needle threader -   Cut-offs bin -   Needle set (ELX 705) -   Tools and accessories in separate box -	Color-coded threading paths	~	~	~	
Stitch length adjustable while sewing···Accessories in looper cover···Sewing lightLEDLEDLEDSafety switch activated when cover open···Technical Data···Overlock seam width 3-7 mm···Coversticch width 2,8/5,6 mm···Coversticch width 3-10 mm···Knife drive from below···7-step presser foot pressure···Rolled hen lever integrated into stitch plate···Standard Accessories···Standard Accessories···Manual needle threader···Cut-offs bin····Needle set (ELX 705)····Dok and accessories in separate box····Dok and accessories in separate box····Dok and accessories in separate box····Standard box······Dok and accessories in separate box·····Dok and accessories in separate box·· <td>Lay-in threading system</td> <td>~</td> <td>~</td> <td>~</td> <td></td>	Lay-in threading system	~	~	~	
Accessories in looper cover          Accessories in looper cover       ✓       ✓         Safety switch activated when cover open       ✓       ✓         Technical Data       ✓       ✓         Overlock seam width 3-7 mm       ✓       ✓         Conversitich width 2,8/5,6 mm       ✓       ✓         Coversitich width 2,8/5,6 mm       ✓       ✓         Coversitich width 2,8/5,6 mm       ✓       ✓         Coversitich width 2,8/5,6 mm       ✓       ✓         Convositich width 2,8/5,6 mm       ✓       ✓         Testp presser foot pressure       ✓       ✓         Accessories       ✓       ✓         Standard Accessories       ✓       ✓         Standard Accessories       ✓       ✓         Manual needle threader       ✓       ✓         Cut-offs bin       ✓       ✓         Needle set (ELX 705)       ✓       ✓         Dols and accessories in separate box       ✓       ✓	Thread tension release when presser foot raised	~	~	~	
Sewing light       LED       LED       LED       LED         Safety switch activated when cover open       ✓       ✓       ✓         Technical Data       ✓       ✓       ✓         Overlock seam width 3-7 mm       ✓       ✓       ✓         Cowerstitch width 2,8/5,6 mm       ✓       ✓       ✓         Cowerstitch width 3-10 mm       ✓       ✓       ✓         Knife drive from below       ✓       ✓       ✓         7-step presser foot pressure       ✓       ✓       ✓         Rolled hen lever integrated into stitch plate       ✓       ✓       ✓         Maximum sewing speed (stitches per minute)       1300       1300       1300         Standard Accessories       ✓       ✓       ✓         Manual needle threader       ✓       ✓       ✓         Averloes t(ELX 705)       ✓       ✓       ✓         Needle set (ELX 705)       ✓       ✓       ✓       ✓         Tools and accessories in separate box       ✓       ✓       ✓       ✓         Tools and accessories in separate box       ✓       ✓       ✓       ✓         Tools and accessories in separate box       ✓       ✓       ✓       ✓       <	Stitch length adjustable while sewing	~	~	~	
Safety switch activated when cover open       ·       ·       ·         Technical Data       ·       ·       ·         Overlock seam width 3-7 mm       ·       ·       ·         Coverstitch width 2.8/5,6 mm       ·       ·       ·         Cowlock seam width 3-10 mm       ·       ·       ·       ·         Knife drive from below       ·       ·       ·       ·         7-step presser foot pressure       ·       ·       ·       ·         Rolled hem lever integrated into stitch plate       ·       ·       ·       ·         Maximum sewing speed (stitches per minute)       1300       1300       1300       1300         Standard Accessories       ·       ·       ·       ·       ·       ·         Standard overlock presser foot       ·       ·       ·       ·       ·       ·       ·       ·       ·       ·       ·       ·       ·       ·       ·       ·       ·       ·       bernetter       ·       ·       ·       ·       ·       ·       ·       ·       ·       ·       ·       ·       ·       ·       ·       bernetter       ·       ·       ·       bernetter	Accessories in looper cover	~	~	~	▲ bernette
Technical DataImage: Construction of the	Sewing light	LED	LED	LED	
Overlock seam width 3-7 mm···Coverstitch width 2,8/5,6 mm····Combo stitch width 3-10 mm····Knife drive from below····7-step presser foot pressure····Rolled hem lever integrated into stitch plate···Maximum sewing speed (stitches per minute)130013001300Standard Accessories···Standard overlock presser foot···Upper looper converter···Maual needle threader···Cut-offs bin···Needle set (ELX 705)···Tools and accessories in separate box···	Safety switch activated when cover open	~	~	~	
Coverstitch width 2,8/5,6 mm···Combo stitch width 3–10 mm····Knife drive from below····7-step presser foot pressure····Rolled hem lever integrated into stitch plate····Maximum sewing speed (stitches per minute)1300130013001300Standard Accessories····Standard overlock presser foot····Manual needle threader·····Cut-offs bin·····bernetteNeedle set (ELX 705)·····bernetteTools and accessories in separate box·····bernette	Technical Data				
Coverstitch width 2,8/5,6 mmImage: Coverstitch width 3,-10 mmImage: Coverstitch width 3,-10 mmCombo stitch width 3,-10 mmImage: Coverstitch width 3,-10 mmImage: Coverstitch width 3,-10 mmKnife drive from belowImage: Coverstitch width 3,-10 mmImage: Coverstitch width 3,-10 mm7-step presser foot pressureImage: Coverstitch width 2,8/5,6 mmImage: Coverstitch width 3,-10 mm7-step presser foot pressureImage: Coverstitch width 2,8/5,6 mmImage: Coverstitch width 2,8/5,6 mmRolled hem lever integrated into stitch plateImage: Coverstitch Image: Coverstitch Width 2,8/5,6 mmImage: Coverstitch Width 2,8/5,6 mmMaximum sewing speed (stitches per minute)130013001300Standard AccessoriesImage: Coverstitch Width 2,8/5,6 mmImage: Coverstitch Width 2,8/5,6 mmStandard overlock presser footImage: Coverstitch Width 2,8/5,6 mmImage: Coverstitch Width 2,8/5,6 mmManual needle threaderImage: Coverstitch Width 2,8/5,6 mmImage: Coverstitch Width 2,8/5,6 mmCut-offs binImage: Coverstitch Width 2,8/5,6 mmImage: Coverstitch Width 2,8/5,6 mmNeedle set (ELX 705)Image: Coverstitch Width 2,8/5,6 mmImage: Coverstitch Width 2,8/5,6 mmTools and accessories in separate boxImage: Coverstitch Width 2,8/5,6 mmImage: Coverstitch Width 2,8/5,6 mmTools and accessories in separate boxImage: Coverstitch 2,8/5,6 mmImage: Coverstitch 2,8/5,6 mmTools and accessories in separate boxImage: Coverstitch 2,8/5,6 mmImage: Coverstitch 2,8/5,6 mmTools and accessories in separate boxImage: Coverstitch 2,8/5,6	Overlock seam width 3–7 mm	~	$\checkmark$	-	
Knife drive from belowImage: Constraint of the belowImage: Constraint of the belowImage: Constraint of the below7-step presser foot pressureImage: Constraint of the belowImage: Constraint of the belowImage: Constraint of the belowRolled hem lever integrated into stitch plateImage: Constraint of the belowImage: Constraint of the belowImage: Constraint of the belowRolled hem lever integrated into stitch plateImage: Constraint of the belowImage: Constraint of the belowImage: Constraint of the belowMaximum sewing speed (stitches per minute)Image: Constraint of the belowImage: Constraint of the belowImage: Constraint of the belowStandard overlock presser footImage: Constraint of the belowImage: Constraint of the belowImage: Constraint of the belowUpper looper converterImage: Constraint of the belowImage: Constraint of the belowImage: Constraint of the belowCut-offs binImage: Constraint of the belowImage: Constraint of the belowImage: Constraint of the belowNeedle set (ELX 705)Image: Constraint of the belowImage: Constraint of the belowImage: Constraint of the belowTools and accessories in separate boxImage: Constraint of the boxImage: Constraint of the boxImage: Constraint of the box	Coverstitch width 2,8/5,6 mm	~	-	~	bernette
7-step presser foot pressure···Rolled hem lever integrated into stitch plate··-Maximum sewing speed (stitches per minute)130013001300Standard Accessories···Standard overlock presser foot···Upper looper converter···Manual needle threader···Cut-offs bin···Needle set (ELX 705)···Tools and accessories in separate box··	Combo stitch width 3–10 mm	~	-	-	
Rolled hem lever integrated into stitch plate✓✓✓Maximum sewing speed (stitches per minute)130013001300Standard Accessories✓✓✓Standard overlock presser foot✓✓✓Upper looper converter✓✓✓Manual needle threader✓✓✓Cut-offs bin✓✓✓Needle set (ELX 705)✓✓✓Tools and accessories in separate box✓✓	Knife drive from below	~	~	-	
Rolled Hein level integrated into sulch place     Image: Constraint of the set of th	7-step presser foot pressure	~	~	~	
Standard Accessories       Image: Constraint of the sector o		~	~	-	
Standard overlock presser foot       ·       ·       ·         Upper looper converter       ·       ·       ·         Manual needle threader       ·       ·       ·         Cut-offs bin       ·       ·       ·       ·         Needle set (ELX 705)       ·       ·       ·       bernette	Maximum sewing speed (stitches per minute)	1300	1300	1300	
Upper looper converter       ·       ·       ·         Manual needle threader       ·       ·       ·         Cut-offs bin       ·       ·       ·         Needle set (ELX 705)       ·       ·       ·         Tools and accessories in separate box       ·       ·       ·					
Manual needle threader     Image: Cut-offs bin     Image: Cut-of	Standard overlock presser foot	~	~	~	
Cut-offs bin	Upper looper converter	~	~	-	
Needle set (ELX 705) Dernette	Manual needle threader	~	~	~	
Tools and accessories in separate box	Cut-offs bin	~	~	-	
Tools and accessories in separate box	Needle set (ELX 705)	~	~	~	pernette
	Tools and accessories in separate box	~	~	~	
Dust cover tor poly 1000		~	~	~	for my ideas